

CRYSTOR

HYBRID & ELECTRIC VEHICLES

AERTRON 0W-30 C2 HPF



CRYSTOR RANGE

14 products · 8 grades

SAE 0W-8	1	SAE 0W-12	1
SAE 0W-16	1	SAE 0W-20	1
SAE 0W-30	1	SAE 5W-30	1
SAE 5W-40	2	SAE 75W-70	1

SPECIFICATIONS · SAE 0W-30

- API SP/SP-RC
- ACEA C2
- ILSAC GF-6A
- MB 229.61
- MB 227.61-CNG
- FIAT 9.55535-DS1
- FIAT 9.55535-GS1
- RENAULT RN 0700
- CHRYSLER MS13340/MS90047
- BMW LL 12 FE
- BMW LL 19-FE
- FORD 950-A WSS-M2C950-A
- PSA B712312

Fully Synthetic Energy-Efficient Lubricant for Modern Engines Requiring ACEA C2

Fully synthetic SAE 0W-30 for modern engines requiring ACEA C2. Intended to protect the engine and the operation of the catalyst and particulate filter, with emphasis on energy efficiency and LSPI control.

KEY ADVANTAGES

- High energy efficiency and reduced fuel consumption
- Effective action against LSPI (Low-Speed Pre-Ignition)
- Low coefficient of friction
- Reduced pollutant emissions
- High oxidation stability at the high operating temperatures of modern turbocharged engines

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK160201	18	54 boxes
5 L	GDEK160205	4	50 boxes

CRYSTOR

HYBRID & ELECTRIC VEHICLES

AERTRON OW-30 C2 HPF

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Density at 15°C	kg/m ³	ASTM D1298	853
Kinematic viscosity at 40°C	cSt	ASTM D445	64,52
Kinematic viscosity at 100°C	cSt	ASTM D445	11.12
Viscosity Index	-	ASTM D2270	167
Flash Point	°C	ASTM D92	225
Pour Point	°C	ASTM D97	-45

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.