

POLARON COOLANTS & ANTIFREEZE

CRYSTA 100 G12++ BLUE OAT



POLARON RANGE

19 products · 5 grades

G11	6	G12	3
G12+	2	G12++	3
G13	3		

SPECIFICATIONS · G12++

- Technology: OAT
- CUNA NC 956-16 VW G-12++
- BS 6580 FK Helf R 443 AFNOR R 15/601
- CUMMINS 90T8-4 / 85T8-2
- ASTM D 3306 ASTMD 4985 SAE J 1034 JIS K 2234 UNE26361-88
- EMPA E/L 1415 MIL Italy
- KSM 2142 NATO S 759
- VW TL 774 D/F/G (G12 G12+ G12++)
- VAG (AUDI-SKODA-SEAT-PORSCHE)
- MERCEDES: MB 325.3
- RENAULT 41-01-001
- MAN 248/324 Type SNF
- FORD WSS-M97B44-D / ESD M 97 B49-A / ESE M97B49-A
- CRYSLER MS 9176
- OPEL: GM QL 130100
- GM 1899M
- NAVISTAR B-1 Type III
- VOLVO JOHN DEERE H 24 B1 and C1
- Leyland Trucks LTS 22 AF 10 Mack 014GS17004 PEGASO
- GM US 6277 M C
- Deutz/MWN 0199-2091 WARTSILIA 32-9011

Concentrated OAT Monoethylene Glycol Antifreeze for Aluminium & Light Metal Engines

Concentrated monoethylene glycol antifreeze with OAT technology. For cooling circuits of internal combustion engines made of aluminium alloys and light metals.

KEY ADVANTAGES

- Maximum protection of aluminium alloy engine circuits
- High heat dissipation capacity
- Tracer for quick detection of leaks in the circuit
- Excellent protection of the water pump and all rubber parts
- Raised boiling point
- NAP free (nitrate, amine and phosphate free)

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK90301	18	54 boxes
4 L	GDEK90344	4	60 boxes
5 L	GDEK90305	4	50 boxes
20 L	GDEK90320	—	48 units
60 L	GDEK90360	—	18 units
208 L	GDEK903208	—	4 units
1.000 L	GDEK9031000	—	1 unit

POLARON COOLANTS & ANTIFREEZE

CRYSTA 100 G12++ BLUE OAT

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	ASTM D3306	Blue
Appearance	-	ASTM D3306	Limpid
Density	kg/dm ³	ASTM D3306	1,13
pH (50% dilution)	-	ASTM D3306	8,4
Boiling point	°C	ASTM D1120	197
Freezing point (50% dilution)	°C	ASTM D1177	-36
Glass corrosion test	mg/specimen	ASTM D1384	Pass

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.