

AUTRON

AUTOMATIC TRANSMISSION FLUIDS

DRIVON ATF IID



AUTRON RANGE

8 products · Automatic Transmission Fluids

SPECIFICATIONS

- GM DEXRON IID
- MAN 339 Z1, V1
- ALLISON C3
- MB 236.3
- ZF TE-ML 03D, 04D, 09, 11, 14A, 17C

Mineral Dexron II D Fluid for Automatic Transmissions & Torque Converters

High viscosity index mineral automatic transmission fluid for compatible automatic gearboxes, torque converters and hydraulic systems requiring the Dexron II D performance level. It may be used in selected power steering systems or manual gearboxes only where specified by the manufacturer.

KEY ADVANTAGES

- High thermal and oxidative stability
- Maximum resistance to wear
- Maximum compatibility with materials used in these systems
- Low pour point
- Immediate control response even at low temperatures

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK50001	18	54 boxes
4 L	GDEK50044	4	60 boxes
20 L	GDEK50020	—	48 units
60 L	GDEK50060	—	18 units

AUTRON

AUTOMATIC TRANSMISSION FLUIDS

DRIVON ATF IID

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Red
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,857
Kinematic viscosity at 40°C	cSt	ASTM D445	43
Kinematic viscosity at 100°C	cSt	ASTM D445	7,5
Viscosity Index	-	ASTM D2270	141
Flash Point	°C	ASTM D92	222
Pour Point	°C	ASTM D97	-40

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.