

AUTRON

AUTOMATIC TRANSMISSION FLUIDS

DURAVEX ATF HD



AUTRON RANGE

8 products · Automatic Transmission Fluids

SPECIFICATIONS

- ZF TE-ML 04D ZF TE-ML 14 A/C
- ZF TE-ML 16M ZF TE-ML 16S
- ZF TE-ML 20C ZF TE-ML 25C
- MAN 339 TYPE V3/Z3/Z12
- MB 236.9/236.91/238.22
- VOLVO 97340/97341
- ALLISON TES 668 TES 295
- ALLISON TES 495
- APPROVED VOITH 150.014524.XX
- VOITH H55.6336.XX DIWA.5
- DIWA.6
- SFU IVECO 18-1807 CLASS AG3

Synthetic Fluid for Heavy-Duty Automatic Transmissions of Trucks & Buses

Synthetic automatic transmission fluid for heavy-duty vehicles and buses operating under increased loads and demanding duty cycles. It is intended for compatible transmissions where enhanced thermo-oxidative resistance and extended drain intervals are specified, always within the manufacturer's limits.

KEY ADVANTAGES

- Very high thermal and oxidative stability
- Dissipation of generated heat
- Exceptional friction control
- Maximum resistance to wear
- Maximum compatibility with materials used in these systems

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK50401	18	54 boxes
4 L	GDEK50444	4	60 boxes
20 L	GDEK50420	—	48 units
60 L	GDEK50460	—	18 units

AUTRON

AUTOMATIC TRANSMISSION FLUIDS

DURAVEX ATF HD

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,841
Kinematic viscosity at 40°C	cSt	ASTM D445	38
Kinematic viscosity at 100°C	cSt	ASTM D445	7,3
Viscosity Index	-	ASTM D2270	160
Flash Point	°C	ASTM D92	224
Pour Point	°C	ASTM D97	-52

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.