

MAXTOR TRUCKS & HEAVY DUTY

DYNATOR 0W-20 FE



MAXTOR RANGE

14 products · 8 grades

SAE 0W-20	1	SAE 5W-20	1
SAE 5W-30	3	SAE 5W-40	1
SAE 10W-30	1	SAE 10W-40	2
SAE 15W-40	4	SAE 20W-50	1

SPECIFICATIONS · SAE 0W-20

- SFU IVECO 18-1804 CLASSE TLV-LS

Fully Synthetic Low-SAPS Lubricant for Heavy-Duty Diesel Engines

Fully synthetic SAE 0W-20 lubricant for selected heavy-duty diesel engines requiring a specialized Low SAPS formulation. The registered Group IV/V base oils are oriented towards low friction and engine protection, in line with the specific OEM requirements.

KEY ADVANTAGES

- Low friction coefficient
- Anti-oxidation action against degradation of the lubricant
- High thermal stability
- High detergency
- High dispersancy, anti-corrosion and anti-rust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK21505	4	50 boxes
20 L	GDEK21520	—	48 units
60 L	GDEK21560	—	18 units
208 L	GDEK215208	—	4 units
1.000 L	GDEK2151000	—	1 unit

MAXTOR TRUCKS & HEAVY DUTY

DYNATOR OW-20 FE

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,848
Kinematic viscosity at 40°C	cSt	ASTM D445	48,3
Kinematic viscosity at 100°C	cSt	ASTM D445	8,95
Viscosity Index	-	ASTM D2270	168
Flash Point	°C	ASTM D92	229
Freezing point	°C	ASTM D97	-43

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.