

MAXTOR TRUCKS & HEAVY DUTY

FERON 5W-40 LOW SAPS



MAXTOR RANGE

14 products · 8 grades

SAE 0W-20	1	SAE 5W-20	1
SAE 5W-30	3	SAE 5W-40	1
SAE 10W-30	1	SAE 10W-40	2
SAE 15W-40	4	SAE 20W-50	1

SPECIFICATIONS · SAE 5W-40

- API CK4/CJ-4/CI-4+/CI-4/CH-4
- ACEA E11/E9/E7/
- DTFR 15C110 (MB 228.51) DTFR 15C100 (MB 228.31)
- VOLVO VDS-4 .5
- VOLVO VDS-4
- VOLVO VDS-3
- RENAULT RLD-3
- MACK EO-O PREMIUM PLUS
- MACK EOS-4.5
- MAN3477/3575/3271-1
- MTU 3.1/2.1
- CUMMINS CES 20081 CUNNINS CES 20086
- DEUTZ DQC IV-10 LA/III-10LA/IV-18LA/III-18LA
- DETROIT DIESEL 93K218 /93K222
- CATERPILLAR ECF-3/ECF-2/ECF-1A
- JASO DH-1 JASO DH-2
- MTU TYPE 2.1
- MTU TYPE 3.1

Low SAPS Synthetic-Based Lubricant for Turbocharged Heavy-Duty Diesel Engines

Synthetic-based SAE 5W-40 Low SAPS lubricant for heavy-duty diesel engines. Intended for compatible applications with EGR, turbocharging and DPF systems, where fitted, with emphasis on lubricating protection under demanding thermal operation.

KEY ADVANTAGES

- Low friction for better protection
- Counteraction against the molecular oxidation of the lubricant
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK20205	4	50 boxes
20 L	GDEK20220	—	48 units
60 L	GDEK20260	—	18 units
208 L	GDEK202208	—	4 units
1.000 L	GDEK2021000	—	1 unit

MAXTOR TRUCKS & HEAVY DUTY

FERON 5W-40 LOW SAPS

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,858
Kinematic viscosity at 40°C	cSt	ASTM D445	84,2
Kinematic viscosity at 100°C	cSt	ASTM D445	14,2
Viscosity Index	-	ASTM D2270	175
Flash Point	°C	ASTM D92	229
Pour Point	°C	ASTM D97	-35

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.