

GEARTRON

GEAR OILS

FLEXTRON 75W-80 MTF SYN



GEARTRON RANGE

9 products · 6 grades

SAE 75W	1	SAE 75W-80	2
SAE 75W-90	2	SAE 75W-140	1
SAE 80W-90	2	SAE 85W-90	1

SPECIFICATIONS · SAE 75W-80

- API GL-4/GL4+
- ZF TE ML 16K
- MB 235.10
- BMW MTF LT-2/LT3/LT4
- PSA B712330/ B712315/9730A8
- C550 CITROEN C1
- GM 1940182
- GM 1940768
- FORD WSD M2C200-D / WSS M2C200-C
- NISSAN MTX-XZ/TL HONDA MTF/ MTFII/ MTFIII
- FIAT 9.55550-MZ1/MZ6/MZ7
- VOLVO 97308/97309/97310
- VW G009317

Synthetic Gear Lubricant for Manual & Synchronised Gearboxes

Synthetic SAE 75W-80 for manual and synchronized gearboxes, as well as compatible transmission units. Designed for applications with API GL-4/GL-4+ requirements, with emphasis on gear protection and correct transmission operation.

KEY ADVANTAGES

- Optimised load resistance and reduced operating losses
- Very high thermal and oxidative stability
- Outstanding friction control
- Maximum resistance to wear
- Maximum compatibility with materials used in these systems

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK51601	18	54 boxes
4 L	GDEK51644	4	60 boxes
20 L	GDEK51620	—	48 units
60 L	GDEK51660	—	18 units
208 L	GDEK516208	—	4 units

GEARTRON

GEAR OILS

FLEXTRON 75W-80 MTF SYN

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,850
Kinematic viscosity at 40°C	cSt	ASTM D445	44
Kinematic viscosity at 100°C	cSt	ASTM D445	8,9
Viscosity Index	-	ASTM D2270	188
Flash Point	°C	ASTM D92	220
Pour Point	°C	ASTM D97	-51

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.