

ALIMENTRON

FOOD-GRADE LUBRICANTS

FOODTRON ISO VG 220 FG



ALIMENTRON RANGE

4 products · 4 grades

ISO VG 32	1	ISO VG 46	1
ISO VG 68	1	ISO VG 220	1

SPECIFICATIONS · ISO VG 220

- ISO VG 220
- Formulato con prodotti approvati FDA 21 CFR 178.3620(b) NSF H1

ISO VG 220 Lubricant for Food, Cosmetic and Pharmaceutical Production Machinery

For mechanical systems in food, cosmetics and pharmaceutical production that require the corresponding viscosity grade. Possible product contact is assessed solely on the basis of documentation.

KEY ADVANTAGES

- Chemical inertness
- Maximum oxidation stability
- Hydrolytic stability
- Excellent material compatibility
- High anti-corrosion and anti-rust properties
- High anti-foaming capacity

PACK	CODE	UNITS / BOX	PER PALLET
20 L	GDEK140320	—	48 units
208 L	GDEK1403208	—	4 units
1.000 L	GDEK14031000	—	1 unit

ALIMENTRON

FOOD-GRADE LUBRICANTS

FOODTRON ISO VG 220 FG

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Density at 15°C	kg/m ³	ASTM D1298	850
Kinematic viscosity at 40°C	cSt	ASTM D445	220
Kinematic viscosity at 100°C	cSt	ASTM D445	11,11
Viscosity index	-	ASTM D2270	155
Flash Point	°C	ASTM D92	280
Pour Point	°C	ASTM D97	-41

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.