ALIMENTRON FOOD-GRADE LUBRICANTS

FOODTRON ISO VG 68 FG

ALIMENTRON RANGE

4 products · 4 grades

ISO VG 32	1	ISO VG 46	1
ISO VG 68	1	ISO VG 220	1

SPECIFICATIONS · ISO VG 68

- ISO VG 68
- Formulato con prodotti approvati FDA 21 CFR 178.3620(b) NSF H1

Multifunctional Lubricant for Food, Cosmetic and Pharmaceutical Industrial Machinery

Multi-purpose lubricant for industrial equipment in food, cosmetics and pharmaceutical facilities. Its use requires appropriate documentation for each application.

KEY ADVANTAGES

- Chemical inertness
- Maximum oxidation stability
- Hydrolytic stability
- Excellent material compatibility
- High anti-corrosion and anti-rust properties
- High anti-foaming capacity

PACK	CODE	UNITS / BOX	PER PALLET
20 L	GDEK140220	–	48 units
208 L	GDEK1402208	–	4 units
1.000 L	GDEK14021000	–	1 unit

ALIMENTRON FOOD-GRADE LUBRICANTS

FOODTRON ISO VG 68 FG

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Density at 15°C	kg/m^3	ASTM D1298	**830**
Kinematic viscosity at 40°C	cSt	ASTM D445	**68**
Kinematic viscosity at 100°C	cSt	ASTM D445	**11,11**
Viscosity index	-	ASTM D2270	**155**
Flash Point	°C	ASTM D92	**246**
Pour Point	°C	ASTM D97	**-49**

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.

"Blended with German Traditional Crafts."