

HYDRONIX

HYDRAULIC FLUIDS

HYDRAVERA ISO VG 32 ECO HEES



HYDRONIX RANGE

15 products · 3 grades

ISO VG 32	5	ISO VG 46	5
ISO VG 68	5		

SPECIFICATIONS · ISO VG 32

- ISO VG 32
- ECOLABEL CONTRATTO N° IT/027/008/001
- DIN ISO 15380 HEES
- SFU PARKER DENISON HF-1/HF-2/HF-6
- SFU EATON BROVHUR 3-401/2010

Environmentally Compatible HEES Hydraulic Fluid ISO VG 32 with High Biodegradability

ISO VG 32 hydraulic fluid for applications requiring increased environmental compatibility, with low aquatic toxicity and high biodegradability according to the manufacturer's description. Intended for compatible hydraulic circuits, to be selected based on the manufacturer's instructions.

KEY ADVANTAGES

- High biodegradability and low aquatic toxicity
- High viscosity index, to operate even under severe temperature changes
- Maximum oxidation stability
- Hydrolytic stability
- High anti-corrosion and anti-rust properties
- High anti-foaming capacity

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK150005	4	50 boxes
20 L	GDEK150020	—	48 units
208 L	GDEK1500208	—	4 units
1.000 L	GDEK15001000	—	1 unit

HYDRONIX

HYDRAULIC FLUIDS

HYDRAVERA ISO VG 32 ECO HEES

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Density at 15°C	kg/m ³	ASTM D1298	900
Kinematic viscosity at 40°C	cSt	ASTM D445	34,6
Kinematic viscosity at 100°C	cSt	ASTM D445	8,42
Viscosity index	-	ASTM D2270	231
Flash Point	°C	ASTM D92	252
Pour point	°C	ASTM D97	<-18

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.