

OCEANIX

MARINE

MARINE SEA-TECH 10W-30 4T



OCEANIX RANGE

6 products · 3 grades

SAE 10W-30

2

SAE 15W-40

1

SAE 20W-50

1

SPECIFICATIONS · SAE 10W-30

- API SL/SM
- NMMA FC-W CATALYST
- MERCURY-MARINE TOHATSU
- HONDA-MARINE EVINRUDE
- YAMAHA JOHNSON
- VOLVO PENTA SEA.DOO
- SUZUKI-MARINE
- MARINER BOMBARDIER

Synthetic Four-Stroke Marine Oil SAE 10W-30 for Outboard & Inboard Gasoline Engines

Synthetic SAE 10W-30 lubricant for four-stroke petrol engines of outboard and inboard boats. Its formulation focuses on thermo-oxidative stability and on limiting spark plug deposits, supporting engine cleanliness and protection in demanding marine operating conditions.

KEY ADVANTAGES

- Excellent thermo-oxidative resistance
- Clean combustion without deposits
- Prevention of carbon deposits on the pistons
- Maximum cleanliness of the combustion chamber
- Exceptional pre-ignition protection

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK100201	18	54 boxes
4 L	GDEK100244	4	60 boxes
20 L	GDEK100220	—	48 units
60 L	GDEK100260	—	18 units
208 L	GDEK1002208	—	4 units
1.000 L	GDEK10021000	—	1 unit

OCEANIX

MARINE

MARINE SEA-TECH 10W-30 4T

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,862
Kinematic viscosity at 40°C	cSt	ASTM D445	70
Kinematic viscosity at 100°C	cSt	ASTM D445	11,8
Viscosity index	-	ASTM D2270	165
Flash Point	°C	ASTM D92	230
Pour point	°C	ASTM D97	-38

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.