

CRYSTOR

HYBRID & ELECTRIC VEHICLES

NEXIVA 0W-8 HPF



CRYSTOR RANGE

14 products · 8 grades

SAE 0W-8	1	SAE 0W-12	1
SAE 0W-16	1	SAE 0W-20	1
SAE 0W-30	1	SAE 5W-30	1
SAE 5W-40	2	SAE 75W-70	1

SPECIFICATIONS · SAE 0W-8

- SAE J300
- HTHS ≥ 1.7 mPa·s

Fully Synthetic Extra-Low-Viscosity Lubricant for Hybrid Petrol Engines & Range Extenders

Fully synthetic SAE 0W-8 ultra-low-viscosity lubricant for compatible HEV, PHEV and MHEV hybrid petrol engines and range extender engines. It focuses on reducing internal friction and on lubrication during frequent start-stop cycles. HTHS ≥ 1.7 mPa·s.

KEY ADVANTAGES

- Extra-low SAE 0W-8 viscosity for reduced internal friction
- Lubrication during frequent start-stop cycles
- For compatible HEV, PHEV, MHEV and range-extender petrol engines
- HTHS ≥ 1.7 mPa·s

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK160601	18	54 boxes
5 L	GDEK160605	4	50 boxes

CRYSTOR

HYBRID & ELECTRIC VEHICLES

NEXIVA 0W-8 HPF

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Density	kg/m ³	ASTM D1298	845
Kinematic viscosity at 40°C	cSt	ASTM D445	26.2
Kinematic viscosity at 100°C	cSt	ASTM D445	5.4
Viscosity Index	-	ASTM D2270	147
Flash Point	°C	ASTM D92	224
Freezing point	°C	ASTM D97	-48

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.