

GEARTRON

GEAR OILS

NOVASTRONG 75W MTF



GEARTRON RANGE

9 products · 6 grades

SAE 75W	1	SAE 75W-80	2
SAE 75W-90	2	SAE 75W-140	1
SAE 80W-90	2	SAE 85W-90	1

SPECIFICATIONS · SAE 75W

- API GL-4
- BMW/ MINI 83220306816
83220397244 83222409710
MTF-LT-3 DTF-1
- CITROEN JWS2271 1618078480
- FORD WSS-M2C200-D2/D3/E1
- FORD C-MAX MONDEO S-MAX
TRANSIT FOCUS HONDA MTFIII
- FIAT 9.55550-MZ6
- MB 235.73
- MB 235.10
- PSA B71 2316
- PSA B71 2317
- VOLVO C30/C70 S40/60 V50/70
1161839 1161838
- VW TL 521-71 VW TL 521-78 VW
TL G052 171-A1 G052 178 A2
G052 512 A2
- VW TL 726 G052726A2
G055726A2 G060726A2
G070726A2

Low-Viscosity Synthetic Lubricant for Manual Gearboxes

Synthetic low viscosity SAE 75W lubricant for compatible manual gearboxes. It focuses on protecting the transmission mechanisms and limiting friction losses, supporting efficient operation where specified by the manufacturer.

KEY ADVANTAGES

- Optimised shifting performance
- Maximum shear stability
- Very high thermal and oxidative stability
- Exceptional friction control
- Maximum compatibility with materials used in these systems
- Immediate control response even at low temperatures

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK52101	18	54 boxes
4 L	GDEK52144	4	60 boxes
20 L	GDEK52120	—	48 units
60 L	GDEK52160	—	18 units
208 L	GDEK521208	—	4 units

GEARTRON

GEAR OILS

NOVASTRONG 75W MTF

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,852
Kinematic viscosity at 40°C	cSt	ASTM D445	30
Kinematic viscosity at 100°C	cSt	ASTM D445	6,1
Viscosity Index	-	ASTM D2270	156
Flash Point	°C	ASTM D92	221
Pour Point	°C	ASTM D97	-52

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.