

## OCEANIX

## MARINE

# OCEATRON 2T DFI



### OCEANIX RANGE

6 products - 3 grades

|            |   |            |   |
|------------|---|------------|---|
| SAE 10W-30 | 2 | SAE 15W-40 | 1 |
| SAE 20W-50 | 1 |            |   |

### SPECIFICATIONS

- API TC
- 2 STROKE DFI
- NMMA-TC W3 NMMA-TC-WII
- ISO L-EGC ISO L-EGD
- JASO FD / FC
- MERCURY DFI 2-T
- EVINRUDE E-TEC ENGINES

## Fully Synthetic Two-Stroke Oil for DFI Outboard Gasoline Engines

Fully synthetic total-loss lubricant for two-stroke direct fuel injection (DFI) outboard petrol engines. Intended for the specific lubrication requirements of this technology, aiming at stable delivery and protection of engine components. Use and method of supply must be consistent with the manufacturer's instructions.

### KEY ADVANTAGES

- Clean combustion without deposits
- Prevention of carbon deposits on the pistons
- Maximum cleanliness of the combustion chamber
- Exceptional protection against pre-ignition
- Excellent oxidation stability

| PACK    | CODE         | UNITS / BOX | PER PALLET |
|---------|--------------|-------------|------------|
| 1 L     | GDEK100501   | 18          | 54 boxes   |
| 4 L     | GDEK100544   | 4           | 60 boxes   |
| 20 L    | GDEK100520   | —           | 48 units   |
| 60 L    | GDEK100560   | —           | 18 units   |
| 208 L   | GDEK1005208  | —           | 4 units    |
| 1.000 L | GDEK10051000 | —           | 1 unit     |

OCEANIX

MARINE

## OCEATRON 2T DFI

## TYPICAL CHARACTERISTICS

| Property                     | Unit               | Method     | Typical value |
|------------------------------|--------------------|------------|---------------|
| Colour                       | -                  | Visual     | Blue          |
| Appearance                   | -                  | Visual     | Limpid        |
| Density                      | kg/dm <sup>3</sup> | ASTM D7042 | 0,84          |
| Kinematic viscosity at 40°C  | cSt                | ASTM D445  | 38            |
| Kinematic viscosity at 100°C | cSt                | ASTM D445  | 7,1           |
| Viscosity index              | -                  | ASTM D2270 | 151           |
| Flash Point                  | °C                 | ASTM D92   | 118           |
| Pour point                   | °C                 | ASTM D97   | -32           |

## MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

## SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.