MOTRONIX MOTORCYCLES

RACETORA 5W-40 4T

MOTRONIX RANGE

19 products · 13 grades

SAE 5W	1	SAE 5W-40	2
SAE 5W-50	1	SAE 10W	1
SAE 10W-40	2	SAE 10W-50	2
SAE 10W-60	1	SAE 15W	1
SAE 15W-40	1	SAE 15W-50	1
SAE 15W-60	1	SAE 20W-40	1
SAE 20W-50	1		

SPECIFICATIONS · SAE 5W-40

- API SP/ SN/SM
- JASO T903 JASO MA-MA2
- JASO Quality Category SP

Four-Stroke Motorcycle Engine Oil SAE 5W-40 for Road Bikes & Recreational Vehicles

SAE 5W-40 lubricant for four-stroke road motorcycle engines and selected ATV, SXS or other recreational vehicle applications, where this grade is specified. Designed for demanding operating conditions. Wet clutch suitability and the JASO specification must match the manual and the current TDS.

KEY ADVANTAGES

- Maximum heat dissipation
- Excellent oxidation stability
- High resistance to pre-ignition
- Low pour point and very high viscosity index, ensuring maximum protection even with extreme temperature fluctuations
- High detergent, anti-corrosion and anti-rust properties

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK40901	18	54 boxes
4 L	GDEK40944	4	60 boxes
20 L	GDEK40920	–	48 units
60 L	GDEK40960	–	18 units
208 L	GDEK409208	–	4 units
1.000 L	GDEK4091000	–	1 unit

MOTRONIX MOTORCYCLES

RACETORA 5W-40 4T

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	**Amber**
Appearance	-	Visual	**Limpid**
Density	kg/dm^3	ASTM D7042	**0,855**
Kinematic viscosity at 40°C	cSt	ASTM D445	**95,85**
Kinematic viscosity at 100°C	cSt	ASTM D445	**14,8**
Viscosity index	-	ASTM D2270	**161**
Flash Point	°C	ASTM D92	**228**
Pour point	°C	ASTM D97	**-37**

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.

"Blended with German Traditional Crafts."