

MAXTOR TRUCKS & HEAVY DUTY

STRATRON 5W-30 FA-4



MAXTOR RANGE

14 products · 8 grades

SAE 0W-20	1	SAE 5W-20	1
SAE 5W-30	3	SAE 5W-40	1
SAE 10W-30	1	SAE 10W-40	2
SAE 15W-40	4	SAE 20W-50	1

SPECIFICATIONS · SAE 5W-30

- API FA-4
- DAIMLERV TRUCK DTFR 15C130 –
- MB 228.61
- CUMMINS CES 20087
- JASO DH-2 JASO DH-1 DETROIT DIESEL 93K223
- RENAULT RLD-5
- VOLVO VDS-5
- FORD M2C214-B1

API FA-4 Low-HTHS Synthetic-Based Lubricant for Modern Heavy-Duty Diesel Engines

Specialized synthetic-based SAE 5W-30 lubricant of API FA-4 category, with lower HTHS, for specific modern heavy-duty diesel engines. Designed with a focus on fuel economy and compatible aftertreatment systems. It is not a general replacement for CK-4 products.

KEY ADVANTAGES

- High energy efficiency supporting reduced fuel consumption
- Low friction coefficient
- Counteraction against the molecular oxidation of the lubricant
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK20005	4	50 boxes
20 L	GDEK20020	–	48 units
60 L	GDEK20060	–	18 units
208 L	GDEK200208	–	4 units
1.000 L	GDEK2001000	–	1 unit

MAXTOR TRUCKS & HEAVY DUTY

STRATRON 5W-30 FA-4

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,858
Kinematic viscosity at 40°C	cSt	ASTM D445	61,8
Kinematic viscosity at 100°C	cSt	ASTM D445	10,6
Viscosity Index	-	ASTM D2270	163
Flash Point	°C	ASTM D92	229
Pour Point	°C	ASTM D97	-35

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.