

INDUSTRIAL

INDUSTRIAL LUBRICANTS

UTENSIL ISO VG 32 SLIDE



INDUSTRIAL RANGE

28 products · 9 grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 150	4	ISO VG 220	3
ISO VG 320	2	ISO VG 460	2
ISO VG 680	1		

SPECIFICATIONS · ISO VG 32

- DIN 51502 CGLP
- ISO 6743-13 ISO 19378 ISO-L-GA ISO-L-GB
- ISO 12925-1 ISO 6743-6 ISO-L-CKC ISO-L-CKE
- ISO 6743-4 ISO 11158 ISO-L-HM
- CINCINNATI MILACRON P53 (ISO VG 32)
- STANIMUC G 32

Slideway and Hydraulic Lubricant for Machine Tools, Lifts and Hoists

Circulation or total-loss system lubricant for hydraulic applications and loaded guideways/slideways of machine tools, machinery, elevators and goods lifts. Special additives provide anti-stick properties and reduced dripping.

KEY ADVANTAGES

- Multifunctionality (slideway function combined with hydraulic and gear functions)
- Anti-drip
- Anti-friction
- No stick-slip
- EP protection

PACK	CODE	UNITS / BOX	PER PALLET
20 L	GDEK70020	—	48 units
208 L	GDEK700208	—	4 units
1.000 L	GDEK7001000	—	1 unit

INDUSTRIAL INDUSTRIAL LUBRICANTS

UTENSIL ISO VG 32 SLIDE

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Density at 15°C	kg/m ³	ASTM D1298	855
Kinematic viscosity at 40°C	cSt	ASTM D445	32
Kinematic viscosity at 100°C	cSt	ASTM D445	5.6
Viscosity index	-	ASTM D2270	110
Flash Point	°C	ASTM D92	224
Pour Point	°C	ASTM D97	-20

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.