

CRYSTOR

HYBRID & ELECTRIC VEHICLES

VELTRON 5W-30 504/507



CRYSTOR RANGE

14 products · 8 grades

SAE 0W-8	1	SAE 0W-12	1
SAE 0W-16	1	SAE 0W-20	1
SAE 0W-30	1	SAE 5W-30	1
SAE 5W-40	2	SAE 75W-70	1

SPECIFICATIONS · SAE 5W-30

- API SN
- ACEA C3
- MB 229.31/229.51/229.52
- BMW LL-04
- VW 504.00/507.00
- PORSCHE C30
- GM DEXOS 2
- PSA B712297

Synthetic Reduced-Ash Lubricant for Engines Requiring VW 504.00/507.00

Synthetic SAE 5W-30 lubricant with a stated formulation of Group IV/V base oils and reduced-ash additives. Intended for compatible engines that require the stated specifications VW 504.00/507.00, with emphasis on oxidation stability and on the operation of exhaust aftertreatment systems.

KEY ADVANTAGES

- High oxidation stability at the high operating temperatures of modern turbocharged engines
- Reduced pollutant emissions
- Low coefficient of friction
- Low pour point and very high viscosity index for protection across wide temperature changes

PACK	CODE	UNITS / BOX	PER PALLET
1L	GDEK160301	18	54 boxes
5 L	GDEK160305	4	50 boxes

CRYSTOR

HYBRID & ELECTRIC VEHICLES

VELTRON 5W-30 504/507

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Density at 15°C	kg/m ³	ASTM D1298	854
Kinematic viscosity at 40°C	cSt	ASTM D445	62,87
Kinematic viscosity at 100°C	cSt	ASTM D445	10,77
Viscosity Index	-	ASTM D2270	164
Flash Point	°C	ASTM D92	229
Pour Point	°C	ASTM D97	-40

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.