

GEARTRON

GEAR OILS

ZENTORA 75W-140 LS



GEARTRON RANGE

9 products · 6 grades

SAE 75W	1	SAE 75W-80	2
SAE 75W-90	2	SAE 75W-140	1
SAE 80W-90	2	SAE 85W-90	1

SPECIFICATIONS · SAE 75W-140

- API GL-5 LS
- API MT-1
- MIL L-2105 C/D
- SAE J2360
- ARVINMERITOR 076-A
- FORD WSP-M2C197-A/M2C192-A
- SCANIA STO 1:0
- SCANIA STO 2:0A
- MAN 342 M2
- MB 235.61
- ZF TE-ML 05C/12D/16G/18/21C

Ester-Based Synthetic Lubricant for Heavily Loaded Limited-Slip Differentials

Ester-based synthetic SAE 75W-140 for limited-slip differentials (LS/LSD) operating under increased loads. Focuses on friction control and wear protection in API GL-5 LS applications. Not intended in general for synchronized gearboxes without a relevant application approval.

KEY ADVANTAGES

- Optimised differential performance thanks to the correct friction coefficient value
- Very high thermal and oxidative stability
- Exceptional friction control
- Maximum resistance to wear
- Maximum compatibility with materials used in these systems

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK51101	18	54 boxes
4 L	GDEK51144	4	60 boxes
20 L	GDEK51120	—	48 units
60 L	GDEK51160	—	18 units
208 L	GDEK511208	—	4 units

GEARTRON

GEAR OILS

ZENTORA 75W-140 LS

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,875
Kinematic viscosity at 40°C	cSt	ASTM D445	168
Kinematic viscosity at 100°C	cSt	ASTM D445	27
Viscosity Index	-	ASTM D2270	205
Flash Point	°C	ASTM D92	22
Pour Point	°C	ASTM D97	-45

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.